

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

Generated Part Number

GDCX-PA-44

Part Number Builder

GDCX-P	–	A		44		
Series		Panel Stop Option	Shield Option	Positions & Contacts	Keyed Option	Plating Option

MODULAR JACKS AND PLUGS: GDCX-P Series
Vertical Through Hole

Product Features
Available in 4, 6, and 8 Position Housings
Vertical Mount
Through Hole Contacts
CSA/NRTL Certified File No. LR78160
UL File No. E134345

Performance Specifications
Materials and Finish
Housing Material
PBT Thermoplastic, UL 94V-0 Rated, Black Color
Contact Material
Phosphor Bronze

Electrical Characteristics
Insulation Resistance
500 Megohms Min.
Dielectric Withstanding Voltage
1000V RMS, 60Hz
Contact Resistance
20 milliohms Max.
Voltage Rating
125V DC
Current Rating
1.5A
Operating Temperature
-40°C to +85°C
Durability Rating
500 Mating Cycles Min.

Series
GDCX-P - Perpendicular Through Hole Modular Jacks

Panel Stops
A - With Panel Stops
N - Without Panel Stops

Shield Options
Blank - Non-Shielded
S - Shielded (Available Only with 8P8C Option)

Number of Positions / Contacts
44 - 4 Postions / 4 Contacts
64 - 6 Positions / 4 Contacts
66 - 6 Positions / 6 Contacts
88 - 8 Positions / 8 Contacts

Keyed Option
Blank - Not Keyed
K - Keyed (Only for 8P8C)

Plating Option
Blank - Gold Flash
50 - 50µ" Gold Plating

Contact Kycon for Other Options

GDCX-Px-88
Dimensions in mm

