CERAMIC


Band Pass Filter

BFCN-1860+

50Ω 1580 to 2200 MHz

THE BIG DEAL

- Small Size, 3.2 × 1.6 mm
- Good VSWR, 1.5:1 Typ. at Passband
- Temperature Stable
- Hermetically Sealed
- LTCC Construction



Generic photo used for illustration purposes only

CASE STYLE: FV1206-4

+RoHS Compliant
The +Suffix identifies RoHS Compliance.
See our website for methodologies and qualifications

APPLICATIONS

- Harmonic Rejection
- Transmitters/Receivers

PRODUCT OVERVIEW

The BFCN-1860+ LTCC band pass filter covers the 1580 to 2200 MHz passband with 2 dB passband insertion loss and 20 dB upper/lower stopband rejection. This model handles up to 2.5 W RF input power and provides a wide operating temperature range from -55 to +100 °C. Utilizing LTCC multi-layer construction, the filter achieves excellent repeatability of performance and comes in a tiny 1206 ceramic package with wraparound terminations, minimizing performance variations due to parasitics and saving space in dense PCB layouts.

KEY FEATURES

Features	Advantages
Small Size, 3.2 × 1.6 mm	Saves space in dense circuit boards and minimizes the effects of parasitics.
LTCC Construction	Provides a rugged package that is well suited for tough environments including high humidity and high temperature extremes.
Wrap-Around Terminations	Provides excellent solderability and easy visual inspection capability.
Wide operating temperature range, -55 to +100 °C	Enables reliable performance in extreme environments

Band Pass Filter

BFCN-1860+

50Ω 1580 to 2200 MHz

ELECTRICAL SPECIFICATIONS[1,2] AT +25 °C

Parameter		F#	Frequency (MHz)	Min.	Typ.	Max.	Units
Passband	Center Frequency	-			1860		MHz
	Insertion Loss	F1-F2	1580-2200		2.0	3.5	dB
	VSWR	F1-F2	1580-2200		1.5	2.5	:1
Stop Band, Lower	Insertion Loss	DC-F3	1300		20		dB
	VSWR	DC-F3	1300		20		:1
Stop Band, Upper	Insertion Loss	F4-F5	2600-4800		20		dB
	VSWR	F4-F5	2600-4800		15		:1

1. Measured on Mini-Circuits Characterization Test Board TB-BFCN-1860+.
2. This filter is not intended for use as a DC blocking circuit element. In applications where DC voltage is present at either input or output ports, blocking capacitors are required at the corresponding RF port.


ABSOLUTE MAXIMUM RATINGS

Parameter	Ratings
Operating Temperature	-55 °C to +100 °C
Storage Temperature	-55 °C to +100 °C
RF Power Input[3]	2.5 W at +25 °C

3. Passband rating, derate linearly to 0.7 W at +100 °C ambient.

Permanent damage may occur if any of these limits are exceeded.

TYPICAL FREQUENCY RESPONSE




CERAMIC

Band Pass Filter


BFCN-1860+

50Ω 1580 to 2200 MHz

FUNCTIONAL SCHEMATIC



CASE STYLE DRAWING




PAD CONNECTIONS

RF IN	1
RF OUT	3
GROUND	2,4

PRODUCT MARKING: F8

DEMO BOARD P/N: TB-BFCN-1860+

SUGGESTED PCB LAYOUT (PL-454)




NOTES:
1. TRACE WIDTH PARAMETERS ARE SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS .0066"±.0007". COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH AND GAP MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.

DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER).

DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK.

PCB Land Pattern



Suggested Layout,
Tolerance to be within ±.002

OUTLINE DIMENSIONS (Inches / mm)

A	B	C	D	E	F	G	H	J
.126	.063	.037	.026	.075	.012	.182	.104	.069
3.20	1.60	0.94	0.66	1.91	0.30	4.62	2.64	1.75

K	L	M	N	P	Q	R	wt
.119	.041	.039	.013	.024	.020	.039	grams
3.02	1.04	0.99	0.33	0.61	0.51	0.99	.020

TAPE & REEL INFORMATION: F75

CERAMIC


Band Pass Filter


BFCN-1860+


50Ω 1580 to 2200 MHz


TYPICAL PERFORMANCE DATA AT +25 °C

Full Band Performance			Pass Band Performance		
Frequency (MHz)	Insertion Loss (dB)	VSWR (:1)	Frequency (MHz)	Insertion Loss (dB)	Group Delay (nsec)
10	81.30	72.38	1580	1.78	1.06
40	72.24	67.32	1600	1.71	0.98
100	57.92	60.68	1620	1.66	0.93
400	35.41	43.01	1640	1.62	0.87
1000	24.12	22.58	1660	1.61	0.82
1300	19.87	10.75	1700	1.58	0.75
1580	1.78	1.10	1750	1.56	0.70
1660	1.61	1.38	1800	1.54	0.66
2000	1.56	1.55	1850	1.53	0.63
2200	2.00	1.74	1900	1.53	0.62
2600	24.98	5.02	1950	1.54	0.62
3000	27.70	17.47	2000	1.56	0.62
3500	37.29	23.88	2050	1.60	0.64
4100	31.00	24.03	2100	1.68	0.66
4800	30.01	2.93	2200	2.00	0.74









NOTES

A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.

C. The parts covered by this specification document are subject to Mini-Circuits' standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the standard terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/terms/viewterm.html