

# Git


medowhill

# Git

- Backup
- Cooperation

# Configuration

- /etc/gitconfig
- ~/.gitconfig
- .git/config
- \$ git config --global user.name [user name]
- \$ git config --global user.email [user email]
- \$ git config --global core.editor [editor name]




A screenshot of a terminal window titled "jaeminhong — ubuntu@ip-172-31-4-3: ~ — ssh -i medowhill\_1.pem ubuntu@52.79.88.53 — 80x13". The terminal shows the following commands and their output:

```
[ubuntu@ip-172-31-4-3:~$ git config --global user.name "Jaemin Hong"
[ubuntu@ip-172-31-4-3:~$ git config --global user.email hjm0901@gmail.com
[ubuntu@ip-172-31-4-3:~$ git config --global core.editor vim
[ubuntu@ip-172-31-4-3:~$ git config --list
user.name=Jaemin Hong
user.email=hjm0901@gmail.com
core.editor=vim
[ubuntu@ip-172-31-4-3:~$ cat ~/.gitconfig
[user]
    name = Jaemin Hong
    email = hjm0901@gmail.com
[core]
    editor = vim
```

# Initialize & Remote Repository

- \$ git init
- \$ git remote add [name] [url]



```
[jaeminhong@ip-172-31-4-3 ~]$ ssh -i medowhill_1.pem ubuntu@52.79.88.53
[ubuntu@ip-172-31-4-3:~/workspace/test]$ git init
Initialized empty Git repository in /home/ubuntu/workspace/test/.git/
[ubuntu@ip-172-31-4-3:~/workspace/test]$ git remote add origin https://github.com/Medowhill/gitseminarprac.git
[ubuntu@ip-172-31-4-3:~/workspace/test]$ git remote -v
origin  https://github.com/Medowhill/gitseminarprac.git (fetch)
origin  https://github.com/Medowhill/gitseminarprac.git (push)
```

# Clone

- \$ git clone [url]

```
[jaeminhong@ip-172-31-4-3: ~workspace] jaeminhong — ubuntu@ip-172-31-4-3: ~workspace/gitseminarprac — ssh -i medowhill_1.pem ubuntu@52.7...
[ubuntu@ip-172-31-4-3:~/workspace]$ git clone https://github.com/Medowhill/gitseminarprac.git
Cloning into 'gitseminarprac'...
warning: You appear to have cloned an empty repository.
Checking connectivity... done.
[ubuntu@ip-172-31-4-3:~/workspace$ cd gitseminarprac/
[ubuntu@ip-172-31-4-3:~/workspace/gitseminarprac$ git remote -v
origin  https://github.com/Medowhill/gitseminarprac.git (fetch)
origin  https://github.com/Medowhill/gitseminarprac.git (push)
```

# Status

- \$ git status


```
[jaeminhong@ip-172-31-4-3: ~workspace/test]$ ssh -i medowhill_1.pem ubuntu@52.79.88.53 -l jaeminhong
[ubuntu@ip-172-31-4-3:~/workspace/test]$ git status
On branch master

Initial commit

Untracked files:
  (use "git add <file>..." to include in what will be committed)

    Hello.scala


nothing added to commit but untracked files present (use "git add" to track)
```



# Add


- \$ git add [file]

```
jaeminhong — ubuntu@ip-172-31-4-3: ~/workspace/test — ssh -i medowhill_1.pem ubuntu@52.79.88.53 —...  
[ubuntu@ip-172-31-4-3:~/workspace/test$ git add Hello.scala  
[ubuntu@ip-172-31-4-3:~/workspace/test$ git status  
On branch master  
  
Initial commit  
  
Changes to be committed:  
(use "git rm --cached <file>..." to unstage)  
  
    new file:   Hello.scala
```



# Commit

- \$ git commit



```
[ubuntu@ip-172-31-4-3:~/workspace/test$ git commit  
[master (root-commit) db5f5a4] First commit - add Hello.scala file  
1 file changed, 5 insertions(+)  
create mode 100644 Hello.scala  
[ubuntu@ip-172-31-4-3:~/workspace/test$ git status  
On branch master  
nothing to commit, working directory clean
```

```
[ubuntu@ip-172-31-4-3:~/workspace/test$ vim Hello.scala  
[ubuntu@ip-172-31-4-3:~/workspace/test$ git status  
On branch master  
Changes not staged for commit:  
(use "git add <file>..." to update what will be committed)  
(use "git checkout -- <file>..." to discard changes in working directory)  
  
modified:   Hello.scala  
  
no changes added to commit (use "git add" and/or "git commit -a")
```

# .gitignore

- Specify files do not want to track

```
[ubuntu@ip-172-31-4-3:~/workspace/test$ scalac Hello.scala
[ubuntu@ip-172-31-4-3:~/workspace/test$ git status
On branch master
Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git checkout -- <file>..." to discard changes in working directory)

    modified:   Hello.scala

Untracked files:
  (use "git add <file>..." to include in what will be committed)

    Hello$.class
    Hello.class

no changes added to commit (use "git add" and/or "git commit -a")
[ubuntu@ip-172-31-4-3:~/workspace/test$ vim .gitignore
[ubuntu@ip-172-31-4-3:~/workspace/test$ git status
On branch master
Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git checkout -- <file>..." to discard changes in working directory)

    modified:   Hello.scala

Untracked files:
  (use "git add <file>..." to include in what will be committed)

    .gitignore

no changes added to commit (use "git add" and/or "git commit -a")]
```

# More on Add

- \$ git add -p



```
[ubuntu@ip-172-31-4-3:~/workspace/test$ git add -p Hello.scala
diff --git a/Hello.scala b/Hello.scala
index 900e5ea..214eae1 100644
--- a/Hello.scala
+++ b/Hello.scala
@@ -1,5 +1,6 @@
 object Hello {
    def main(args: Array[String]) {
        println("Hello world!")
+       println("Hello world!")
    }
}
[Stage this hunk [y,n,q,a,d,/,e,?]?
```

# Undo

- \$ git commit --amend
- \$ git reset HEAD [file]
- \$ git checkout -- [file]

```
[ubuntu@ip-172-31-4-3:~/workspace/test$ git status
On branch master
Changes to be committed:
  (use "git reset HEAD <file>..." to unstage)

    new file:  .gitignore
    modified:  Hello.scala

[ubuntu@ip-172-31-4-3:~/workspace/test$ git reset HEAD Hello.scala
Unstaged changes after reset:
M      Hello.scala
[ubuntu@ip-172-31-4-3:~/workspace/test$ git status
On branch master
Changes to be committed:
  (use "git reset HEAD <file>..." to unstage)

    new file:  .gitignore

Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git checkout -- <file>..." to discard changes in working directory)

    modified:  Hello.scala

[ubuntu@ip-172-31-4-3:~/workspace/test$ git checkout -- Hello.scala
[ubuntu@ip-172-31-4-3:~/workspace/test$ git status
On branch master
Changes to be committed:
  (use "git reset HEAD <file>..." to unstage)

    new file:  .gitignore
```

# Difference

- \$ git diff --staged [file]
- \$ git diff [file]

```
ubuntu@ip-172-31-4-3:~/workspace/test$ git diff --staged
diff --git a/.gitignore b/.gitignore
new file mode 100644
index 0000000..6b468b6
--- /dev/null
+++ b/.gitignore
@@ -0,0 +1 @@
+*.class
diff --git a>Hello.scala b>Hello.scala
index 900e5ea..214eae1 100644
--- a>Hello.scala
+++ b>Hello.scala
@@ -1,5 +1,6 @@
 object Hello {
    def main(args: Array[String]) {
        println("Hello world!")
+       println("Hello world!")
    }
}
```

```
ubuntu@ip-172-31-4-3:~/workspace/test$ vim Hello.scala
ubuntu@ip-172-31-4-3:~/workspace/test$ git diff Hello.scala
diff --git a>Hello.scala b>Hello.scala
index 214eae1..871e682 100644
--- a>Hello.scala
+++ b>Hello.scala
@@ -2,5 +2,6 @@
 object Hello {
    def main(args: Array[String]) {
        println("Hello world!")
        println("Hello world!")
+       println("Hello world!")
    }
}
```

# Log & Show

- \$ git log
- \$ git show [commit]

```
[ubuntu@ip-172-31-4-3:~/workspace/test] jaeminhong — ubuntu@ip-172-31-4-3: ~/workspace/test — ssh -i medowhill_1.pem ubuntu@52.79.88.53 —...  
ubuntu@ip-172-31-4-3:~/workspace/test$ git log  
commit bfa7bfd20e98179f5313e83cc60fb949c026dcf9  
Author: Jaemin Hong <hjm0901@gmail.com>  
Date: Tue Nov 7 07:07:45 2017 +0000  
  
        add gitignore  
  
commit db5f5a49431055ec3d0b687fc1b4b6eb2a55a65  
Author: Jaemin Hong <hjm0901@gmail.com>  
Date: Tue Nov 7 06:39:16 2017 +0000  
  
        First commit - add Hello.scala file  
[ubuntu@ip-172-31-4-3:~/workspace/test$ git show bfa7bf  
commit bfa7bfd20e98179f5313e83cc60fb949c026dcf9  
Author: Jaemin Hong <hjm0901@gmail.com>  
Date: Tue Nov 7 07:07:45 2017 +0000  
  
        add gitignore  
  
diff --git a/.gitignore b/.gitignore  
new file mode 100644  
index 0000000..6b468b6  
--- /dev/null  
+++ b/.gitignore  
@@ -0,0 +1 @@  
+*.class  
diff --git a/Hello.scala b/Hello.scala  
index 900e5ea..214eae1 100644  
--- a/Hello.scala  
+++ b/Hello.scala  
@@ -1,5 +1,6 @@  
object Hello {  
    def main(args: Array[String]) {  
        println("Hello world!")  
+       println("Hello world!")  
    }  
}
```

# Push & Pull

- \$ git push [repo] [branch]
- --set-upstream
- push.default = simple
- \$ git push
- credential.helper = store
- \$ git pull

```
[jaeminhong@ip-172-31-4-3:~/workspace/test]$ git push origin master  
Username for 'https://github.com': Medowhill  
Password for 'https://Medowhill@github.com':  
Counting objects: 7, done.  
Compressing objects: 100% (5/5), done.  
Writing objects: 100% (7/7), 576 bytes | 0 bytes/s, done.  
Total 7 (delta 1), reused 0 (delta 0)  
remote: Resolving deltas: 100% (1/1), done.  
To https://github.com/Medowhill/gitseminarprac.git  
 * [new branch]      master -> master
```

```
[jaeminhong@ip-172-31-4-3:~/workspace/test]$ git push --set-upstream origin master  
Username for 'https://github.com': Medowhill  
Password for 'https://Medowhill@github.com':  
Branch master set up to track remote branch master from origin.  
Everything up-to-date  
[jaeminhong@ip-172-31-4-3:~/workspace/test]$ git config --global push.default simple  
[jaeminhong@ip-172-31-4-3:~/workspace/test]$ git push  
Username for 'https://github.com': Medowhill  
Password for 'https://Medowhill@github.com':  
Everything up-to-date
```


```
[jaeminhong@ip-172-31-4-3:~/workspace/test]$ git config credential.helper store  
[jaeminhong@ip-172-31-4-3:~/workspace/test]$ git push  
Username for 'https://github.com': Medowhill  
Password for 'https://Medowhill@github.com':  
Everything up-to-date  
[jaeminhong@ip-172-31-4-3:~/workspace/test]$ git push  
Everything up-to-date
```

```
[jaeminhong@ip-172-31-4-3:~/workspace/test]$ git pull  
remote: Counting objects: 6, done.  
remote: Compressing objects: 100% (4/4), done.  
remote: Total 6 (delta 2), reused 6 (delta 2), pack-reused 0  
Unpacking objects: 100% (6/6), done.  
From https://github.com/Medowhill/gitseminarprac  
 b9392e5..36b6d51  master    -> origin/master  
Updating b9392e5..36b6d51  
Fast-forward  
  Hello.scala | 1 +  
  1 file changed, 1 insertion(+)
```

# Making Branch


- \$ git branch [branch]
- \$ git checkout [branch]
- \$ git checkout -b [branch]

```
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac] medowhill — ubuntu@ip-172-31-4-8: ~/workspace/gitseminarprac — ssh -i medowhill.pem ubuntu@52.7...  
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git branch  
* master  
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git branch iss53  
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git branch  
iss53  
* master  
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git checkout iss53  
Switched to branch 'iss53'  
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git branch  
* iss53  
master
```




# Merging Branch (Fast-Forward)

- \$ git merge [branch]




```
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git commit  
[hotfix a9a6385] change hello to hi  
1 file changed, 1 insertion(+), 1 deletion(-)  
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git checkout master  
Switched to branch 'master'  
Your branch is up-to-date with 'origin/master'.  
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git merge hotfix  
Updating 36b6d51..a9a6385  
Fast-forward  
Hello.scala | 2 +-  
1 file changed, 1 insertion(+), 1 deletion(-)  
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git log  
commit a9a638567c0b60106cd5f2229b037b89e970af25  
Author: Jaemin Hong <hjm0901@gmail.com>  
Date: Tue Nov 7 14:04:13 2017 +0000  
  
change hello to hi
```



# Deleting Branch

- \$ git branch -d [branch]

```
medowhill — ubuntu@ip-172-31-4-8: ~/workspace/gitseminarprac — ssh -i medowhill.pem ubuntu@52.7...
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git branch
  hotfix
  iss53
* master
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git branch -d hotfix
Deleted branch hotfix (was a9a6385).
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git branch
  iss53
* master
```



# Merging Branch

- \$ git merge [branch]

```
medowhill — ubuntu@ip-172-31-4-8: ~/workspace/gitseminarprac — ssh -i medowhill.pem ubuntu@52.7...
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git merge iss53
Merge made by the 'recursive' strategy.
 Help.scala | 2 ++
 1 file changed, 2 insertions(+)
 create mode 100644 Help.scala

Merge branch 'iss53'

# Please enter a commit message to explain why this merge is necessary,
# especially if it merges an updated upstream into a topic branch.
#
# Lines starting with '#' will be ignored, and an empty message aborts
# the commit.
```

1,1

All

# Resolving Conflicts

```
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git checkout -b iss54
Switched to a new branch 'iss54'
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ vim Hello.scala
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git add Hello.scala
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git commit
[iss54 985469f] fix hi to i love
 1 file changed, 1 insertion(+), 1 deletion(-)
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git checkout master
Switched to branch 'master'
Your branch is ahead of 'origin/master' by 3 commits.
  (use "git push" to publish your local commits)
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ vim Hello.scala
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git add Hello.scala
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git commit
[master 64128b7] revert hi to hello
 1 file changed, 1 insertion(+), 1 deletion(-)
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git merge iss54
Auto-merging Hello.scala
CONFLICT (content): Merge conflict in Hello.scala
Automatic merge failed; fix conflicts and then commit the result.
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git status
On branch master
Your branch is ahead of 'origin/master' by 4 commits.
  (use "git push" to publish your local commits)
You have unmerged paths.
  (fix conflicts and run "git commit")

Unmerged paths:
  (use "git add <file>..." to mark resolution)

    both modified:  Hello.scala

no changes added to commit (use "git add" and/or "git commit -a")]
```

```
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ vim Hello.scala
[object Hello {
<<<<< HEAD
  val hello = "Hello world!"
=====
  val hello = "I love world!"
>>>> iss54

  def main(args: Array[String]) {
    println(hello)
    println(hello)
    println(hello)
    println(hello)
    println(hello)
    println(hello)
  }
  def help: String = "str"
  1,1          Top
```

```
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ vim Hello.scala
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git add Hello.scala
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git status
On branch master
Your branch is ahead of 'origin/master' by 4 commits.
  (use "git push" to publish your local commits)
All conflicts fixed but you are still merging.
  (use "git commit" to conclude merge)

nothing to commit, working directory clean
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git commit
```

# Pushing Branch

- \$ git push [remote] [branch]

```
medowhill — ubuntu@ip-172-31-4-8: ~/workspace/gitseminarprac — ssh -i medowhill.pem ubuntu@52.7...
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git push origin iss54
[Username for 'https://github.com': Medowhill
[Password for 'https://Medowhill@github.com':
Total 0 (delta 0), reused 0 (delta 0)
To https://github.com/Medowhill/gitseminarprac.git
 * [new branch]      iss54 -> iss54
```

# Pull (Revisited)



- \$ git pull
- \$ git fetch
- \$ git merge

```
medowhill — ubuntu@ip-172-31-4-8: ~/workspace/gitseminarprac — ssh -i medowhill.pem ubuntu@52.7...[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git commit[master 8a8afce] add helper function1 file changed, 1 insertion(+)[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git statusOn branch masterYour branch is ahead of 'origin/master' by 1 commit.(use "git push" to publish your local commits)nothing to commit, working directory clean[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git push[Username for 'https://github.com': Medowhill[Password for 'https://Medowhill@github.com':To https://github.com/Medowhill/gitseminarprac.git ! [rejected]      master -> master (fetch first)error: failed to push some refs to 'https://github.com/Medowhill/gitseminarprac.git'hint: Updates were rejected because the remote contains work that you dohint: not have locally. This is usually caused by another repository pushinghint: to the same ref. You may want to first integrate the remote changeshint: (e.g., 'git pull ...') before pushing again.hint: See the 'Note about fast-forwards' in 'git push --help' for details.[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git fetchremote: Counting objects: 3, done.remote: Compressing objects: 100% (1/1), done.remote: Total 3 (delta 1), reused 3 (delta 1), pack-reused 0Unpacking objects: 100% (3/3), done.From https://github.com/Medowhill/gitseminarprac 6fcccdf..d94310b master -> origin/master[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git statusOn branch masterYour branch and 'origin/master' have diverged, and have 1 and 1 different commit each, respectively.(use "git pull" to merge the remote branch into yours)nothing to commit, working directory clean]
```

```
medowhill — ubuntu@ip-172-31-4-8: ~/workspace2/gitseminarprac — ssh -i medowhill.pem ubuntu@52.7...[ubuntu@ip-172-31-4-8:~/workspace2/gitseminarprac$ git commit[master d94310b] add helper function return itself1 file changed, 1 insertion(+)[ubuntu@ip-172-31-4-8:~/workspace2/gitseminarprac$ git push[Username for 'https://github.com': Medowhill[Password for 'https://Medowhill@github.com':Counting objects: 3, done.Compressing objects: 100% (2/2), done.Writing objects: 100% (3/3), 301 bytes | 0 bytes/s, done.Total 3 (delta 1), reused 0 (delta 0)remote: Resolving deltas: 100% (1/1), completed with 1 local object.To https://github.com/Medowhill/gitseminarprac.git 6fcccdf..d94310b master -> master[ubuntu@ip-172-31-4-8:~/workspace2/gitseminarprac$ git statusOn branch masterYour branch and 'origin/master' have diverged, and have 1 and 1 different commit each, respectively.(use "git pull" to merge the remote branch into yours)nothing to commit, working directory clean]
```

# Rebase (1/2)

- \$ git pull --rebase



```
[ubuntu@ip-172-31-4-8:~/workspace2/gitseminarprac$ git commit  
[master d773776] add hello2 val  
1 file changed, 1 insertion(+)  
[ubuntu@ip-172-31-4-8:~/workspace2/gitseminarprac$ git push  
Username for 'https://github.com': Medowhill  
Password for 'https://Medowhill@github.com':  
Counting objects: 3, done.  
Compressing objects: 100% (3/3), done.  
Writing objects: 100% (3/3), 349 bytes | 0 bytes/s, done.  
Total 3 (delta 1), reused 0 (delta 0)  
remote: Resolving deltas: 100% (1/1), completed with 1 local object.  
To https://github.com/Medowhill/gitseminarprac.git  
b3959ee..d773776 master -> master
```

```
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git commit  
[master 145a79e] add one more print  
1 file changed, 1 insertion(+)  
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git pull --rebase  
remote: Counting objects: 3, done.  
remote: Compressing objects: 100% (2/2), done.  
remote: Total 3 (delta 1), reused 3 (delta 1), pack-reused 0  
Unpacking objects: 100% (3/3), done.  
From https://github.com/Medowhill/gitseminarprac  
 b3959ee..d773776 master -> origin/master  
First, rewinding head to replay your work on top of it...  
Applying: add one more print  
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git log  
commit 4f8a91c1fd687aec9864072934a554cf703819ae  
Author: Jaemin Hong <hjm0901@gmail.com>  
Date: Tue Nov 7 14:50:20 2017 +0000  
  
add one more print  
  
commit d77377685785191ff46aa8231b0b78a5ca770d05  
Author: Jaemin Hong <hjm0901@gmail.com>  
Date: Tue Nov 7 14:49:42 2017 +0000  
  
add hello2 val
```

# Rebase (2/2)

- \$ git checkout [branch1]
- \$ git rebase [branch0]
- \$ git checkout [branch0]
- \$ git merge [branch1]

```
medowhill — ubuntu@ip-172-31-4-8: ~/workspace/gitseminarprac — ssh -i medowhill.pem ubuntu@52.7...[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git checkout -b hotfix
Switched to a new branch 'hotfix'
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ vim Student.scala
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git add Student.scala
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git commit
[hotfix 25ca676] add student class
 1 file changed, 1 insertion(+)
 create mode 100644 Student.scala
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git checkout master
Switched to branch 'master'
Your branch is ahead of 'origin/master' by 1 commit.
  (use "git push" to publish your local commits)
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ vim Hello.scala
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git add Hello.scala
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git commit
[master 2f55b39] add one more print
 1 file changed, 1 insertion(+)
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git checkout hotfix
Switched to branch 'hotfix'
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git rebase master
First, rewinding head to replay your work on top of it...
 Applying: add student class
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git checkout master
Switched to branch 'master'
Your branch is ahead of 'origin/master' by 2 commits.
  (use "git push" to publish your local commits)
[ubuntu@ip-172-31-4-8:~/workspace/gitseminarprac$ git merge hotfix
Updating 2f55b39..704e67c
Fast-forward
  Student.scala | 1 +
  1 file changed, 1 insertion(+)
  create mode 100644 Student.scala
```

# Reference

- <https://git-scm.com/book/ko/v2>